

TREE PROTECTION DETAIL

NO SCALE

- 1. Either plastic or wood, orange snow fencing of 4-foot height shall be installed at or beyond the dripline, unless more substantial fencing is required.
- 2. Stakes shall be 5' metal "T" poles spaced no further apart than 4' on center.
- 3. Fencing shall not be installed closer to the tree than the dripline of those trees to be saved. Special circumstances shall be reviewed by the City.
- 4. Fencing shall be erected prior to any construction activity. The City shall be notified once the fencing is installed for inspection.
- $5.\,$ Under no arcumstance shall the protective fencing be removed without proper approval from the City.
- 6. No person shall conduct any activity within the areas proposed to remain.
 This shall include, but not be limited to:

 a. No solvents or chemicals within the protected areas.

 b. No building materials or construction equipment within the protected areas.

 - c. No grade changes, including fill, within the protected areas.
 - d. No removal of vegetation from the ground up without permission from the City.
 - e. Any required swale needs to be directed around the protected areas. In instances where swales are approved through a protected area, the swales need to be HAND DUG. Machinery of any kind is prohibited.
- 7. Regulated Woodlands or Regulated Trees adjacent to the property are also required to be protected.
- 8. See Section 9.1000 Tree Regulations of the Gresham Community Development Code. Contact Gresham Planning Services at (503) 618-2842